

LANITZ-PRENA FOLIEN FACTORY GmbH

issuing date: 24.08.2009

last updated on: 24.08.2009

1 of 7

product: **ORACOLOR®** matt finish

1. Identification of the substance and supplier

product's name:

name: **ORACOLOR®** matt finish

art.-no.:100-995

supplier:

LANITZ-PRENA FOLIEN FACTORY GmbH

Am Ritterschlösschen 20

04179 Leipzig

Germany

phone: +49-341 / 44 23 05-0

fax: +49-341 / 44 23 05-99

E-mail: Info@oracover.de

Responsible department: laboratory phone: +49-341/44230534
 Emergency phone: poisoning emergency number Berlin/Germany phone: +49-30/30686790
 (consultation in English and German)

2. Composition / Information on ingredients

chemical characteristics: plastic resin, high-molecular, solvent based
 state of aggregation: liquid
 colour: whitish
 odour: of solvents

dangerous ingredients:

	n-Butylacetate	Ethylacetate	Diacetonolcohol	Xylole
CAS-No.:	123-86-4	123-42-2	141-78-6	1330-20-7
EC-No.:	204-658-1	204-626-7	205-500-4	215-535-7
symbol:		F, Xi	Xi	Xn,Xi
classification:	R10,R66,R67	R11,R36,R66,R67	R36	R10,R20/21,R38
concentration:	50%	10%	10%	10%

3. Hazards identification

Flammable. Harmful by inhalation and in contact with skin. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

4. First Aid Measures

General advices:

Bring concerned persons out of the hazard zone, respecting your own safety. When unconscious, apply recovery position.

After inhalation:

Move to fresh air, rest half upright position, loosen closing, keep warm. Artificial respiration in case of difficulty in breathing or apnoea, seek medical attention.

After contact with Skin:

Wash immediately with soap and water. Remove contaminated clothing. When irritation persists, seek medical attention.

After contact with Eyes:

Rinse immediately with plenty of water (not less than 10 minutes), hold eyelids away from eyeball. If necessary apply abacterial protective dressing. Seek medical attention!

issuing date: 24.08.2009

last updated on: 24.08.2009

2 of 7

product: **ORACOLOR®** matt finish

After Ingestion:

Seek medical attention immediately. Rinse mouth with water, do not induce vomiting, don't drink anything. Keep concerned person steady.

5. Fire fighting measures

general advices:

keep away from source of ignition, don't smoke, take precautionary measures against static discharge. Cool down closed containers by water-jets, avoiding explosions caused by raised inside pressure.

Extinguishing media:

foam (alcohol resistant), CO², powder, atomised spray (water)

For safety reasons not adequate for extinguishing:

water-jet

Special exposure hazards:

Can cause explosive gas-air mixtures. Due to the content of organic Dissolvers for preparation, dense and black fume will be caused when burning. Burning products or gases can be: carbon monoxide, CO², nitric oxide, water vapour.

Protective equipment:

Wear self contained breathing apparatus, if necessary protective clothing.

6. Accidental release measures

personal protection:

Wear protective clothing. Keep persons away. Ensure adequate ventilation. Avoid breathing vapours, contact with skin and eyes. Keep ignition or heat sources away.

Environmental precautions:

Keep away from drains, surface water, ground water and soil.

If not possible contact responsible authorities.

Methods of clean-up:

Collect released material with inert absorbent (sand, vermiculite, universal absorbent) and dispose according to local regulations.

7. Handling and Storage

handling:

handling precautions:

observe general safety advices when handling with chemicals. Avoid contact with skin and eyes.

Keep box well closed. Ensure good aeration and ventilation at the working place.

Ensure also good ventilation near to bottom (vapour is heavier than air).

Fire and explosion prevention:

Use only in explosion safe area; keep away from sources of ignition; take precautionary measures against static discharge. Vapours are heavier than air and exapate on the bottom. Vapours mixed with air compose an explosive mixture.

storage:

Requirements for storerooms:

Electrical devises must be explosion proof according to technical standards. Floors must be conductive.

Keep boxes well closed and store them upstanding to avoid leakage.

instructions on storage alongside other materials:

store according to national regulations. Keep away from acidic and alkaline materials, oxidisers and combustible materials.

LANITZ-PRENA FOLIEN FACTORY GmbH

issuing date: 24.08.2009

last updated on: 24.08.2009

3 of 7

product: **ORACOLOR®** matt finish

Further information on storage:

Keep only in well closed boxes. Storage in a dry, well ventilated place. Don't expose to heat or direct solar radiation. Keep away from electrical devices and ignition sources. Respect storage regulations on storage of combustible materials. Additionally, national regulations concerning water hazard class and storage of materials that are hazardous to water must be observed.

8. Exposure control/personal protection

Additional advises for designing technical devices:

Assure good ventilation. Assure, if necessary, observation of limit values by technical measures (aspiration).

Ingredients with limit values to observe:

CAS-No.	denotation substance	STEL	max. exposure limit
123-86-4	n-Butylacetat	480 mg/m ³ , 100ppm	=1=
(=1= do not exceed limit value at no time)			
108-88-3	Ethylacetat	1500 mg/m ³ , 400ppm	2(ÜF)
annotation Y – possible risks of harm to the unborn child are not to be feared in case the STELs are respected.			
123-42-2	Diacetonalkohol	96 mg/m ³ , 20ppm	2(ÜF)
danger of absorption by skin (H)			
1330-20-7	Xylol (compound of isomers)	440 mg/m ³ , 100ppm	2(ÜF)
danger of absorption by skin (H)			

Personal protection equipment

respiratory protection:

Avoid inhalation of vapours, atomised spray and aerosols. In case of insufficient ventilation wear suitable respiratory equipment (full face mask/half mask) with adequate filter (type A).

hand protection:

wear suitable protective gloves (multi-layer gloves – observe specifications given by manufacturer). The gloves should be tested for suitability (e. g. mechanical and thermal resistance, compatibility, antistatic). Worn out or damaged gloves must not be used.

When wearing protective gloves, it is advisable to also wear under-gloves of cotton.

eye protection:

As protection against spots of solvents, wear safety glasses with side protection.

skin protection:

Wear suitable protective clothing (impermeable).

General advices:

Do not eat, drink or smoke at the working place. Keep away from foods, drinks and feeding stuff.

9. Physical and chemical properties

state of aggregation: liquid
 colour: whitish
 odour: of solvents

	value / field	unity	method
Flash point:	> 6	°C	DIN 51755
Boiling range:	80 bis 111	°C	DIN 51751
Ignition point:	ca. 420	°C	DIN 51794
Explosion prop: Lower limit:	1,2	Vol. %	

issuing date: 24.08.2009

last updated on: 24.08.2009

4 of 7

product: **ORACOLOR®** matt finish

	Max limit:	11,5	Vol. %
density:		approx. 1	g/cm ³
viscosity:		300 to 400	mPas
Solubility water:	not		

10. Stability and reactivity

This information is based on the data that is available on this product, its ingredients and similar materials.

conditions to avoid:

when all suggested instructions are observed, no dangerous reactions are known.

Materials to avoid:

Keep away from acidic and alkaline materials and oxidisers.

Dangerous products of decomposition:

Under high temperatures, dangerous products of decomposition as carbon monoxide, CO², nitric oxide and vapour can emerge.

When all suggested instructions are observed, **no!**

11. Toxicological information

This information is based on the data that is available on this product, its ingredients and similar materials.

123-86-4	n-Butylacetate	
	acute toxicity (LD 50) oral:	13100 mg/kg (Rat)
	acute toxicity (LD 50) dermal:	>17600 mg/kg (rabbit)
	acute toxicity (LC 50) inhalation:	>21 mg/l 4h (Rat)
	contact with respiratory system:	no information
	Skin contact:	not skin irritating– not sensibilising (guinea pig)
	Eye contact:	light irritations possible (rabbit)
141-78-6	Ethylacetate	
	acute toxicity (LD 50) oral:	5600 mg/kg (Rat)
	acute toxicity (LD 50) dermal:	18000 mg/kg (rabbit)
	acute toxicity (LC 50) inhalation:	58 mg/l 8h (Rat)
	contact with respiratory system:	irritating (nausea, headache, vertigo)
	Skin contact:	not skin irritating (rabbit) – not sensibilising
	Eye contact:	lightly irritating (rabbit) – not sensibilising
123-42-2	Diacetonolcohol	
	acute toxicity (LD 50) oral:	4000 mg/kg (Rat)
	acute toxicity (LD 50) dermal:	13630 mg/kg (rabbit)
	acute toxicity (LC 0) inhalation:	7,2 mg/l 8h (Rat)
	contact with respiratory system:	irritating
	Skin contact:	lightly irritating (rabbit)
	Eye contact:	irritating
1330-20-7	Xylole	
	acute toxicity (LD 50) oral:	4300 mg/kg (Rat)
	acute toxicity (LD 50) dermal:	2000 mg/kg (rabbit)
	acute toxicity (LC 50) inhalation:	6350 mg/l 4h (Rat)
	contact with respiratory system:	light irritations possible (rabbit) – not sensibilising
	Skin contact:	skin irritating (rabbit) – danger of resorption by skin
	Eye contact:	lightly irritating (rabbit) – not sensibilising

When inhaled, the solvent vapours may have the effect of a narcotic in high concentrations and cause harms like irritation of the mucosa and the respiratory system as well as damages on the kidneys and the liver. Additionally there might be disturbances of the central nervous system.

Indications and symptoms: headache, vertigo, fatigue, amyasthenia, rarely unconsciousness.

product: **ORACOLOR®** matt finish

Longer or repeated contact with the product affect the natural greasing of the skin and causes its drying-out. The product can then penetrate the body by the skin.

Spots of the dissolver can cause irritations of the eyes and reversible damages.

12. Ecological information

This information is based on the data that is available on this product, its ingredients and similar materials.

123-86-4	n-Butylacetate	biodegradability:	readily biodegradable 98% 28d
		toxicity for fish:	LC50 62mg/l 96h (Leuciscus idus melanotus)
		toxicity for daphnia:	EC50 72,8mg/l 24h (Daphnia magna – big water flea)
		toxicity for algae:	EC50 675mg/l 72h (Scenedesmus subspicactus)
		toxicity for bacteria:	EC50 959mg/l 18h (Pseudomonas putida)
141-78-6	Ethylacetate	biodegradability:	readily biodegradable 100% 28d
		toxicity for fish:	LC50 230mg/l 96h (Pimephales promelas)
		toxicity for daphnia:	EC50 717mg/l 48h (Daphnia magna – big water flea)
		toxicity for algae:	EC50 3300mg/l 48h (Scenedesmus subspicactus)
		toxicity for bacteria:	EC10 2900mg/l 16h (Pseudomonas putida)
123-42-2	Diacetonalcohol	biodegradability:	readily biodegradable 100% 14d
		toxicity for fish:	LC50 420mg/l 96h (Lepomis macrochirus)
		toxicity for daphnia:	EC50 9000mg/l 24h (Daphnia magna – big water flea)
		toxicity for algae:	IC5 >3300mg/l 168h (Scenedesmus quadricauda)
		toxicity for bacteria:	EC3 825mg/l 16h (Pseudomonas putida)
1330-20-7	Xylole	biodegradability:	biodegradable
		toxicity for fish:	LC50 86mg/l 48h (Leuciscus idus melanotus)
		toxicity for daphnia:	EC50 165mg/l 24h (Daphnia magna – big water flea)
		toxicity for algae:	no information
		toxicity for bacteria:	no information

additional ecological advices:

Keep away from drains, surface water, ground water and soil.

13. Disposal considerations

Don't throw away with household garbage. Avoid penetration into the canalisation.

Has to be disposed according to the local regulations.

Empty box completely and dispose according to local regulations.

Observe European garbage catalogue: the producer of the garbage is responsible for the correct codification and denotation of the litter.

14. transport information

Road transport ADR, RID

UN – No.	1263
Classification	F1
class	3
hazard denotation number	33
Packing group	II
Hazard label	3
Limited quantity (LQ)	LQ6

issuing date: 24.08.2009

last updated on: 24.08.2009

6 of 7

product: **ORACOLOR®** matt finish

Exempted quantity (EQ) E2
Correct technical name paint

Sea transport IMDG

UN – No. 1263
Klasse 3
EmS - Code F-E, S-E
marine pollutant Nein
Verpackungsgruppe II
Gefahrzettel 3
Exempted quantity (EQ) E2
Correct technical name Paint

Air transport ICAO/IATA

UN – No. 1263
Verpackungsgruppe II
PAX 305
CAO 307
Cargo IMP code RFL
Begrenzte Menge (LQ) Y305
Exempted quantity (EQ) E2
Correct technical name Paint

15. Regulatory information

designation according to EC-directives:



F Flammable



Xn Harmful

denotation according to Ordinance on Hazardous Substances: Xylen, Ethylacetate, Diacetonol, Butylacetate

R - phrases:

R 11 Highly Flammable
R 20/21 Harmful by inhalation and in contact with skin
R 36/38 Irritating to eyes and skin
R 66 Repeated contact may cause skin dryness or cracking
R 67 Vapours may cause drowsiness and dizziness

S - phrases

S 2 Keep out of the reach of children
S 16 Keep away from sources of ignition – No smoking
S 24/25 Avoid any inhalation, contact with skin and eyes
S 29/35 Do not empty into drains; dispose of this material and its container in a safe way
S 33 take precautionary measures against static discharges
S 51 Use only in well-ventilated areas

National regulations:

Water hazard class: 2 (hazardous to waters)

bulletin: M017 – solvents (of the German government safety organisation)

issuing date: 24.08.2009

last updated on: 24.08.2009

7 of 7

product: **ORACOLOR®** matt finish

The latest versions of the Ordinance on Hazardous Substances and the Ordinance on General Plant Safety have to be observed strictly.

As protection from hazardous substances also the following regulations have to be observed strictly:

- Mutterschutzrichtlinienverordnung (legal protection of working mothers)
- Jugendarbeitsschutzgesetz (Youth Employment Protection Act)

16. Other information

The information contained in this data sheet is, to the best of our knowledge, true and accurate, but any recommendations or suggestions, which may be made, are without guarantee, since the conditions of use are beyond our control.

The user is responsible for using this product correctly and respecting all regulations.

The information in this safety data sheet cannot be applied to other products. As soon as the product mentioned in this safety data sheet is immingled, mixed, treated with any other materials or worked on, the information in this safety data sheet cannot be applied to the newly emerged material.

Wording of all R-phrases, referred to in section 2:

- R 11 Highly flammable
- R 20/21 Harmful by inhalation and in contact with skin
- R 36 Irritating to eyes
- R 38 Irritating to skin
- R 66 Repeated contact may cause skin dryness or cracking
- R 67 Vapours may cause drowsiness and dizziness

Abbreviations and und Acronyms:

ADR: Accord europeen relatif au transport international des marchandises Dangereuses par Route

= European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Reglement concernant le transport international ferroviaire de marchandises Dangereuses

= Regulations Concerning the International Transport of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods Code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

PAX: Passenger Aircraft

CAO: Cargo Aircraft Only

STEL: Short Term Exposure Limit